


Ningbo ETDZ Drainage Systems



Innovative

Make a drain, make a solution

Ningbo ETDZ Drainage Systems



Ningbo ETDZ drainage system was created by Ningbo ETDZ Holding LTD. which locate in Haishu district of Ningbo, the company is an expert designer and manufacturer of drainage products for kitchen, bath, balcony and outdoor areas of construction with a wide range of styles and sizes, the highest quality and technically superior design make Ningbo ETDZ drains are durable, easy to maintain and clean, As a supplier with solid experience that not just only supply the customers the products but also many constructive suggestions and innovative drainage solutions.

With a flexible manufacture system to meet the requirement of different clients, custom drains can be made for any size situation and also can customize multiple drain outlets for the high flow capacity. Truly know the reputation is only as good as the products' performance, so we do our best to ensure that the products you buy is the right product and that it is installed correctly in order to do its job successfully.


Contact our friendly sales team with your requirements, you will get a quick response.



OEM & ODM service

We are excited to bring you a new place to find innovative solutions, when the standard size drains are not meet your actual usage, please kindly tell us all your problems, we dedicate to solve it and supply you the most suitable drainage products for you.

We are honor and welcome to produce the customer designed products with a high quality and quick delivery.





C08



Stainless DN38-DN50 (Standard DN40, DN50)



Dn50 with EPDM seal ring



Screw thread connections

Water seal traps



Horizontal welded trap Code: A1



Vertical trap insert Code: A3



horizontal trap insert Code: A2



Horizontal PVC trapped gully Code: A4

Choice of accessories



Adjustable pedestals



Polymeric sealant



Water proofing



Eccentric DN40/50 PVC connection




Hook for cover plate



NO FLANGE SERIES

- ★ Made of true stainless steel(SUS304/EN1.4301)
- * A shiny defect free surface finish, minimise cleaning and maintenance
- * Compact, streamlined appearance, give you a cheerful new look
- * Options of dozen of cover grating styles
- ★ Bottom of drain body with a"V"design to facilitate flow of water
- * Flow capability meet European standard En1253
- * Compatible range of indoor drainage with a coordinated design
- * Easy for installation



Linear drain without flange

Connection: Sides out with DN38--DN50(Standard DN40, DN50)

The minimum height is only 67mm, width 70--100mm, length 300--1200mm

Choice of water seal traps A1, A2


With: Options of cover plate, Convenient to unclog

Height adjustable stand tor levelling the cover plate

Trap insert with deodorant function design

Customized available








NSV40-A3








NTH40-A2

square drain without flange





Square drain without flange

Connection: Vertical outlet with DN38-DN50(Standard DN40, DN50

Choice of removable trap insert A3

The minimum height is only 20mm if no trap request

with: Choice of height adjustable stand for levelling the cover plate

Options of cover plate, convenient to unclog

Trap insert with deodorant function design

Customized available

Triangular drain without flange

Connection: Vertical outlet with DN38--DN50(Standard DN40, DN50)

Choice of removable trap insert A1, A2

The minimum height is only 67mm, side of 150-500mm

With: Choice of height adjustable stand for levelling the cover plate

Options of cover plate, convenient to unclog

Trap insert with deodorant function design

Customized available

"L"shape drain without flange

Connection: Horizontal outlet with DN38--DN50 (standard DN40, DN50)

Choice of removable trap insert A1, A2

The minimum height is only 67mm, width of 70--100mm

Height adjustable stand for levelling the cover plate


with: Options of cover plate. convenient to unclog


Choice of end or centrally located outlet

Trap insert with deodorant function design

Customized available


Item	Length(mm)	Width(mm)	Side(mm)	OD(mm)	Drain direction	Height(mm)	Trap	Adjustable stand	Wal
Linear	300~1200	70~100	×	38~50	Horizontal/Vertical	67~100/20~50	A1,A2,A4/A3	T1,T2	×
Square	×	×	150~500	38~50	Horizontal/Vertical	67~100/20~50	A1,A2,A4/A3	T1,T2	×
"L"Shape	300~1200	70~100	×	38~50	Horizontal/Vertical	67~100/20~50	A1,A2,A4/A3	T1,T2	×
Triangular			150~500	38~50	Horizontal/Vertical	67~100/20~50	A1,A2,A4/A3	T1,T2	×
Customized	$\sqrt{}$	$\sqrt{}$	$\sqrt{}$	38~50	Horizontal/Vertical	67~100/20~50	A1,A2,A4/A3	T1,T2	×











Linear drain with 20mm flange

FLH40-A2

Connection: Horizontal outlet with DN38--DN50 (Standard DN40, DN50)

Choice of water seal traps A1, A2

The minimum height is only 67mm, width 70-100mm, length 300-


1200mm


with: Options of cover plate, Convenient to unclog

Height adjustable stand for levelling the cover plate

Trap insert with deodorant function design

Available of custom special size





Linear drain with 20mm flange

Connection: Horizontal outlet with DN50

Removable PVC water seal trap A4, universal outlet with 360° revolve


Height is 100mm, width 70-100mm, length 300-1200mm

with: Options of cover plate, Convenient to unclog

Height adjustable stand for leveling the cover plate

Trap insert with deodorant function design

Available of custom special



Linear drain with 20mm flange and wall design

Connection: Vertical outlet with DN38--DN50(Standard DN40, DN50)

Water seal trap insert A3

The minimum height is only 20mm if no trap request, width 70-100mm


Options of cover plate, Convenient to unclog

with: Choice of height adjustable stand for levelling the cover plate

Trap insert with deodorant function design

Choice of end or centrally located outlet

Available of custom special size



Square drain with 20mm flange

Connection: Horizontal outlet with DN38--DN50(Standard DN40, DN50)

Choice of removable trap insert A1, A2 Height 67-100mm, width of 150-500mm

with: Height adjustable stand for levelling the cover plate

Options of cover plate, convenient to unclog

Trap insert with deodorant function design

Available of custom special size

Triangular drain with 20mm flange and wall design

Connection: Horizontal outlet with DN38—DN50(Standard DN40, DN50)

Choice of trap insert A1, A2

The minimum height is only 67mm

Height adjustable stand for levelling the cover plate

with: Options of cover plate, convenient to unclog

Wall design along the wall for easier to install

 $\label{thm:condition} \textit{Trap insert with deodorant function design, no worry of stench and worm}$

Customized available

"L"shape drain with 20mm flange

Connection: Horizontal outlet with DN50

Removable PVC trap insert A4

Height is 100 mm, customized width 70-100mm

Height adjustable stand for levelling the cover plate


with: Options of cover plate, convenient to unclog


Choice of outlet locate

Trap insert with deodorant function design

Customized available

Item	Length(mm)	Width(mm)	Side(mm)	OD(mm)	Drain direction	Height(mm)	Trap	Adjustable stand	Wal
Linear	300~1200	70~100	Х	38~50	Horizontal/Vertical	67~100/20~50	A1,A2,A4/A3	T1,T2	\checkmark
Square	х	х	150~500	38~50	Horizontal/Vertical	67~100/20~50	A1,A2,A4/A3	T1,T2	√
"L"Shape	300~1200	70~100	Х	38~50	Horizontal/Vertical	67~100/20~50	A1,A2,A4/A3	T1,T2	\checkmark
Triangular			150~500	38~50	Horizontal/Vertical	67~100/20~50	A1,A2,A4/A3	T1,T2	√
Customized	√	√	√	38~50	Horizontal/Vertical	67~100/20~50	A1,A2,A4/A3	T1,T2	√





Linear drain with 20mm flange

Connection: Vertical screw thread outlet with DN38--DN50 (Standard DN40, DN50)

Shallow "V" design of drain body for a quick drainage

Screw thread outlet specially develop for Australia markets

Choice of water seal trap insert A3

with: The minimum height is 53mmt, width 70-100mm, length 300-1200mm


Options of cover plate, Convenient to unclog

Choice of height adjustable stand for levelling the cover plate

Trap insert with deodorant function design

Choice of end or centrally located outlet

Available of custom special size



Linear drain with 20mm flange

Connection: Horizontal outlet with DN38~DN50 (Standard DN40, DN50)

Choice of water seal traps A1, A2

The minimum height is only 67mm, width 70~100mm


Options of cover plate, convenient to unclog

With: Height adjustable stand for levelling the cover plate

Trap insert with deodorant function design, no worry of stench and worm

Choice of end or centrally located outlet

Available of special size



Triangular drain with 20mm flange

Connection: Vertical outlet with DN38~DN50 (Standard DN40, DN50)

Water seal trap insert A3


The minimum height is 35 mm if no trap request

Choice of height adjustable stand for levelling the cover plate

With: Options of cover plate, convenient to unclog

Trap insert with deodorant function design

Available of custom special size



Square drain with 20mm flange

Connection: Vertical outlet with DN38~DN50 (Standard DN40, DN50)

Removable trap insert A3

Choice of height adjustable stand for levelling the cover plate

With: Options of cover plate, convenient to unclog

Trap insert with deodorant function design,

no worry of stench and worm


Available of custom special size

2.							_		
Item	Length(mm)	Width(mm)	Side(mm)	OD(mm)	Drain direction	Height(mm)	Trap	Adjustable stand	Wal
Linear	300~1200	70~100	X	38~50	Horizontal/Vertical	67~100/35~50	A1,A2,A4/A3	T1,T2	\checkmark
Square	х	X	150~500	38~50	Horizontal/Vertical	67~100/35~50	A1,A2,A4/A3	T1,T2	√
"L"Shape	300~1200	70~100	Х	38~50	Horizontal/Vertical	67~100/35~50	A1,A2,A4/A3	T1,T2	\checkmark
Triangular			150~500	38~50	Horizontal/Vertical	67~100/35~50	A1,A2,A4/A3	T1,T2	\checkmark
Customized	√	\checkmark	√	38~50	Horizontal/Vertical	67~100/35~50	A1,A2,A4/A3	T1,T2	√



- * Made of true stainless(SUS304/EN1.4301)
- * A 15mm perimeter angle frame is available to reduce the risk of tile breakages alongside the channel edge.
- * Streamlined shiny metal appearance, give you an eclectic new look
- * Sanded flange design to secure bonding of under tile waterproofing
- * A shiny defect free surface finish, minimise cleaning and maintenance
- * Options of dozen of cover grating style
- * Bottom of drain body with a "V" design to facilitate flow of water
- * Compatible range of indoor drainage with a coordinated design






Linear drain with 20mm flange

Connection: Vertical outlet with DN38~DN50 (Standard DN40, DN50) Water seal trap insert A3

The minimum height is only 20mm if no trap request, width 70~100mm Options of cover plate, Convenient to unclog

With: Choice of height adjustable stand for levelling the cover plate
Trap insert with deodorant function design

Choice of end or centrally located outlet



Linear drain with 20mm flange

Connection: Horizontal outlet with DN50

Removable PVC water seal trap A4, universal outlet with 360° revolve Height is 100mm, width 70~100mm, length 300~1200mm

With: Options of cover plate, Convenient to unclog


Height adjustable stand for levelling the cover plate

Trap insert with deodorant function design, no worry of stench and worm

Available of custom special size



PLH40-A32



Linear drain with 20mm flange

Connection: Horizontal outlet with DN38~DN50 (Standard DN40.DN50)

Choice of water seal traps A1,A2

The minimum height is only 67mm, width 70~100mm, length 300~1200mm Options of cover plate, Convenient to unclog

With: Height adjustable stand for levelling the cover plate

Trap insert with deodorant function design


Available of custom special size

Item	Length(mm)	Width(mm)	Side(mm)	OD(mm)	Drain direction	Height(mm)	Trap	Adjustable stand	Wal
Linear	300~1200	70~100	Х	38~50	Horizontal/Vertical	67~100/20~50	A1,A2,A4/A3	T1,T2	\checkmark
Square	х	x	150~500	38~50	Horizontal/Vertical	67~100/20~50	A1,A2,A4/A3	T1,T2	\checkmark
"L"Shape	300~1200	70~100	Х	38~50	Horizontal/Vertical	67~100/20~50	A1,A2,A4/A3	T1,T2	\checkmark
Triangular			150~500	38~50	Horizontal/Vertical	67~100/20~50	A1,A2,A4/A3	T1,T2	\checkmark
Customized	√	\checkmark	√	38~50	Horizontal/Vertical	67~100/20~50	A1,A2,A4/A3	T1,T2	√



Trench drain system

The trench drain system is designed for a variety of applications, both indoor and outdoors, commercial, industrial and hospital. Drain is more stronger than ordinary cement concrete, which can be installed using existing construction techniques, are simple, econnmic, and heavy duty. The drain channels are easy to install, durable, resistant to many chemicals and solution for freeze, thaw applications, the flow rates equal to or greater than most larger poured-in-place trench drain grates.




- * Consist of grate cover, channel, flange connection and fittings.
- * Made of true stainless SUS304 or SUS316
- * Choice of grate covers, welded wedge wire grate or punched hole grate
- * Channel standard size with length 500~6000mm, height 110mm, width 140mm, thickness 1.2~1.5mm, wedge wire grating height 20mm
- * A high weight capacity with a high passing ability and warping preventing
- * Non-slip design, bumps or EPDM mat
- * High flow capability, meet European standard En 1253
- * Compatible rang of indoor and outdoor drainage areas
- * Custom special size welcomed




Slotted channel

Slotted channels are suited for large areas with low votumes of waste water such as in dining room, meat processors, dishwashing and cooking areas of a kitchen, etc. Neat and unobtrusive, a good chioce as a barrier between designated wet and dry zones.



- * Made of true stainless SUS304 or SUS316
- * Perimeter angle frame is available to reduce the risk of tile breakages along side the channel edge.
- * Available in customized sizes, lenth 1000mm~6000mm, height 65~180mm with or without against wall design, material thickness 1.5mm
- * Easy to clean, the water along the channel bottom to outlet
- * Suit for tiled foor
- * Choice of channel grate locate in the midddle of channel
- * A high weight capacity with a high passing ability and warping preventing
- * Customized size welcomed




- * Made of true stainless SUS304 or SUS316
- * Solid stainless steel bar to prevent channel deformation or movement in load bearing areas.
- * With a standard length 1000mm~6000mm,height65~180mm with or without against wall design,thickness 1.5mm
- * Easy to clean, the water along the channel bottom to outlet
- * Suit for tiled floor
- * Choice of channel grate locate in the middle of channel
- * A high passing ability and warping preventing
- * Customized size welcomed


Typical channel

This type of channel for use with wedge wire grating or punched cover can be used in a range of areas, such as balcony, roof, courtyard, drive way, pool areas and so on.






- *Channel body made of special Aluminum
- *Reinforcing in the channel middle
- *With standard width 85mm, helght 40mm, material thickness of 2mm
- *Option of covers, wedge wire grating or punched grate
- *A high flow capability
- *Easy to clean, the water along the channel bottom to outlet
- *A high passing ability and warping preventing
- *Custom product welcomed



- * Channel body made of special Aluminum
- * With standard width 85mm, height 23mm, material thickness of 2.5mm
- * Option of covers, wedge wire grating or punched grate(see page 3)
- * Streamlined appearance, unique, a cheerful new look
- * Suit for tiled floor such as balcony, courtyard, pool side, walk way
- * Easy to install and clean, the water along the channel bottom to outlet
- * A high weight capacity with a high passing ability and warping preventing
- * Custom product welcomed



- * Channel body made of stainless steel SUS304
- * Standard width 85mm, height 23mm, material thickness of 1.2mm
- * Option of covers, wedge wire grating or punched grate
- * Steamlined appearance, unique, a cheerful new look
- * Suit for tiled floor such as balcony, courtyard, pool side, walk way
- * Easy to install and clean, the water along the channel bottom to outlet
- * A high weight capacity with a high passing ability and warping preventing
- * Custom product welcomed





NINGBO ETDZ HOLDINGS LTD.

Address: 7-10/F., Galaxy Tower, 35 Changchun Road, Ningbo, China

Tel: +86 574 87622713

Email: cunwei_xu@vip.163.com Website: http://www.nbetdz.com